

# D-STAT

## Wrist Straps/Heel Grounders & Accessories



### Wrist Strap- Order# CI-DAWS

- Constructed with 1 meg ohm resistor for safety.
- 8.5' coil cord for added work area movement
- Extra large 10mm socket and stud for maximum static rate removal.
- Banana plug plus alligator clip for use on all grounds or equipment.



### Heel Grounders-Order# CI-HGR1

- 1 meg ohm resistor for safety
- Reversible 1.46" wide heel cup with conductive or dissipative rubber.
- Conductive Surface Resistivity-  $1.5 \times 10^3$  ohm.
- Dissipative Surface Resistivity-  $5 \times 10^9$  ohms
- Decay rate  $< 0.1$  seconds
- 17.32" of conductive ribbon
- 17" Velcro hook & Loop
- Acid, chemical and heat resistant



### Work Surface Grounding Cord- Order# CI-WSGC

- 10mm male snap
- O ring terminal for secure ground connection
- 10' long wire
- Individually bagged
- Includes 10mm standard female snap with rivet



### Work surface Grounding Cord w/Wrist Strap Plugs Order# CI-WSGCWSP

- 10mm male snap
- 15' long wire
- Two banana jack receptacles for wrist straps
- Individually bagged
- Includes standard 10mm female snap with rivet

**CHRISTOPHER**

**Christopher International Inc.**

4000 Dow Rd. Suite 12  
Melbourne, FL 32934

Ph: (321) 242-6207 Fax: (321) 242-6209  
[www.christopherinternational.com](http://www.christopherinternational.com)